

## DC single core aluminium XLPE MDPE power cable



### Description

Single core class 2 aluminium power cable for use in low voltage DC power distribution systems with nominal voltage of 750V/1000v AC (1.2kV DC) between Live and earth / neutral or \*1.8kV between 2 live conductors. . They come in 2 variants, black, or black with a red stripe for easy identification.

#### \*Extract from IEC60502-1

- Cables rated 1kV (Um= 1.2 kV) AC which are designed and tested in accordance with IEC 60502-1 can also be used in DC distribution systems having their nominal voltages 750V DC (with a maximum of 900V DC) between a live conductor and neutral/earth.
- Or greater than or equal to 1.5kV DC (with a maximum 1.8kV DC) between two live conductors.

### Key Features



**Voltage Rating**  
600V-1000V AC  
1.8kV DC



**Minimum Bending Radius**  
15 x Overall Diameter



**Temperature Limits**  
Maximum operating temperature of conductor: +90°C  
Maximum short-circuit temperature up to 5 sec: +250°C

### Core Colours

#### Sheath identification

1 Core:  Black

1 Core:  Black with  Red stripe

### Standards

- BS EN/IEC 60502-1
- BS EN/IEC 60228

### Construction

- **Conductor:** Class 2 Stranded Aluminium Conductor
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Sheath:** Medium Density Polyethylene (MDPE)

### QA Lab

#### Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



#### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



### Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



#### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

#### ecovadis

## DC single core aluminium XLPE MDPE power cable - Dimensions

Reference	Conductor Size (mm <sup>2</sup> )	Nominal Conductor Diameter	Sheath Thickness (mm)	Minimum Bending Radius	Overall Diameter(mm)	Weight(Kg/Km)
DC1X400MDPE/AD7	400	27.8	1.32	456	30.4	1320

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.