

# DNO Approved SNE Aluminium Split Concentric Cable - XLPE LSZH - 25mm<sup>2</sup> to 35mm<sup>2</sup>



## Description

Used by Distribution Network Operators (DNOs) such as UKPN, ENW, NPG, SSE etc to provide the final connection to domestic properties.

Suitable for sub main distribution boxes, Street lighting systems and high rise buildings.

SNE (Separate Neutral & Earth) construction for use in older installations.

#### **Key Features**



Voltage Rating 600/1000 Volts



Minimum Bending Radius 8 x Overall Diameter



Flame Retardancy BS EN 60332-1-2



**Temperature Limits** Temperature Range: -15°C to + 70°C

#### **Standards**

- BS7870-3-21 for PVC sheath BS7870-3-22 for LSZH sheath
- BS EN/IEC 60332-1-2
- BS EN/IEC 60228

# Construction

- Conductor: Solid Aluminium Conductor
- Insulation: Cross Linked polyethylene (XLPE)
- Bedding: Available in both Poly Vinyl Chloride (PVC) and Low Smoke Zero Halogen (LSZH)
- Neutral Conductor: Plain copper wire covered in blue polymeric compound
- String Separator: Non Hygroscopic separator
- Earth Continuity Conductor: Plain Copper
- Separator: Binding Tape Helically Applied
- Outer Sheath: Low Smoke Zero Halogen (LSZH)
- Sheath Colour: Orange

# **QA Lab**

## Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







# CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



#### **Our Sustainability Commitment**

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



#### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

# ecovadis



















# $DNO\ Approved\ SNE\ Aluminium\ Split\ Concentric\ Cable\ -\ XLPE\ LSZH\ -\ 25mm^2\ to\ 35mm^2\ -\ Dimensions$

Reference	Conductor Size (mm2)	No Of Cores	Max Voltage Rating	Overall Diameter(mm)	Weight(Kg/Km)
25SPLITCONALLSZH	25	1	0.6/1KV	15	490
3X25SPLITCONALOR	25	3	0.6/1KV	23.5	830
35SPLITCONALLSZH	35	1	0.6/1KV	16	610
3X35SPLITCONALOR	35	3	0.6/1KV	26	1030

















CONCENTRIC CABLE CURRENT CARRYING CAPACITY								
	NOMINAL CROSS SECTIONAL	CONTINUOUS CURRENT RATING						
NUMBER OF CORES	AREA	CLIPPED DIRECT	IN CONDUIT ON WALL	IN AIR				
	(MM2)	AMPS	AMPS	AMPS				
1	25	119	105	127				
3	25	90	84	97				
1	35	147	128	158				
3	35	112	103	120				



















## CONCENTRIC CABLE ELECTRIC CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C	MAXIMUM AC RESISTANCE OF CONDUCTOR AT 20°C -	MAXIMUM DC RESISTANCE OF CONCENTRIC CONDUCTOR AT 20°C -
(MM2)	Ω/ΚΜ	Ω/ΚΜ	Ω/ΚΜ
25	1.2	1.54	1.3
35	0.868	1.11	0.91

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

















