

Drinking Water Cable - BS6920, EPDM - 1.5mm² to 95mm²



Description

This cable is designed for the operation of submersible pumps for drinking water, fishponds, swimming pools and in electrical installations in the food and drink manufacturing industry. They are designed for permanent immersion and are non toxic and water proof.

Flatform version available on request.

Key Features



Voltage Rating
450/750 Volts

Core Colours

2 Core: Brown Blue

3 Core: Brown Blue Green Yellow

4 Core: Brown Black Grey Green Yellow

Standards

- WRAS approved to BS6920
- HD22.12.S1

Construction

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

Drinking Water Cable - BS6920, EPDM - 1.5mm² to 95mm² - Dimensions

| Reference | Conductor Size (mm ²) | No Of Cores | Stranding(mm) | Overall Diameter(mm) | Weight(Kg/Km) |
|-------------|-----------------------------------|-------------|---------------|----------------------|---------------|
| DRINK3X1/5R | 1.5 | 3 | 30/0.20 | 10 | 96 |
| DRINK4X1/5R | 1.5 | 4 | 30/0.25 | 11.5 | 125 |
| DRINK3X2/5R | 2.5 | 3 | 50/0.25 | 12 | 148 |
| DRINK4X2/5R | 2.5 | 4 | 50/0.25 | 13.5 | 191 |
| DRINK1X4 | 4 | 1 | 56/0.30 | 6.9 | 67 |
| DRINK3X4R | 4 | 3 | 56/0.30 | 13.80 | 210 |
| DRINK4X4R | 4 | 4 | 56/0.30 | 15.2 | 265 |
| DRINK1X6 | 6 | 1 | 84/0.30 | 7.68 | 92 |
| DRINK3X6R | 6 | 3 | 84/0.30 | 15.5 | 290 |
| DRINK4X6R | 6 | 4 | 84/0.30 | 17.1 | 372 |
| DRINK1X10 | 10 | 1 | 80/0.40 | 9.02 | 136 |
| DRINK3X10R | 10 | 3 | 80/0.40 | 21 | 500 |
| DRINK4X10R | 10 | 4 | 80/0.40 | 23 | 635 |
| DRINK1X16 | 16 | 1 | 126/0.40 | 10.18 | 197 |
| DRINK3X16R | 16 | 3 | 126/0.40 | 24 | 603 |
| DRINK4X16R | 16 | 4 | 126/0.40 | 26 | 900 |
| DRINK1X25 | 25 | 1 | 196/0.40 | 12.25 | 302 |
| DRINK3X25R | 25 | 3 | 196/0.40 | 28 | 1060 |
| DRINK4X25R | 25 | 4 | 196/0.40 | 31.1 | 1380 |
| DRINK1X35 | 35 | 1 | 276/0.40 | 14.1 | 415 |
| DRINK3X35R | 35 | 3 | 276/0.40 | 33 | 1415 |
| DRINK4X35R | 35 | 4 | 276/0.40 | 35.1 | 1835 |
| DRINK1X50 | 50 | 1 | 396/0.40 | 15.9 | 565 |
| DRINK3X50R | 50 | 3 | 396/0.40 | 37 | 1960 |
| DRINK4X50R | 50 | 4 | 396/0.40 | 40 | 2545 |
| DRINK1X70 | 70 | 1 | 360/0.50 | 18.15 | 755 |
| DRINK1X95 | 95 | 1 | 457/0.50 | 20.66 | 998 |

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.