

FG16M16 Power Cable - 1.5mm² to 630mm²



Description

FG16M16 Power Cable | 0.6/1kV | Fire Resistant | Cca-s1b,d1,a1

Key Features



Voltage Rating
600/1000 V AC
900/1500 DC
600/1200 Volts AC
1800V DC



Minimum Bending Radius
4 x Overall Diameter



Oils, Greases and Chemicals Resistant
Yes



Flame Retardancy
BS EN/IEC 60332-1-2



Temperature Limits
Temperature Range: -15°C to + 90°C
Maximum short-circuit temperature: 250°C



CPR Compliant
Yes

Core Colours

Single Core : Black

Standards

- EN 50575:2014+A1:2016
- IEC 60228
- IEC 60754-2
- IEC 61034-2
- BS EN/IEC 60332-1-2
- EN 50399
- CEI UNEL 35324
- CEI 20-13
- UNI EN 13501-6

Construction

- **Conductor:** Class 5 flexible, plain copper wire
- **Insulation:** G16 Hard Grade Ethylene Propylene Rubber (HEPR)
- **Filler:** Thermoplastic filler with reduced emission of corrosive gases
- **Outer Sheath:** M16 quality thermoplastic compound
- **Sheath Colour:** Green

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

FG16M16 Power Cable - 1.5mm² to 630mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Max Resistance at 20°C (Ω /km)	Outside Diameter(mm)	Weight(Kg/Km)
FG16M161X1/5	1.5	1	13.3	8.2	75
FG16M161X2/5	2.5	1	7.98	8.7	94
FG16M161X4	4	1	4.95	9.3	113
FG16M161X6	6	1	3.30	9.9	136
FG16M161X10	10	1	1.91	10.9	189
FG16M161X16	16	1	1.21	11.4	246
FG16M161X25	25	1	0.78	13.2	343
FG16M161X35	35	1	0.554	14.6	438
FG16M161X50	50	1	0.386	16.4	590
FG16M161X70	70	1	0.272	18.3	785
FG16M161X95	95	1	0.206	20.4	1003
FG16M161X120	120	1	0.161	22.4	1250
FG16M161X150	150	1	0.129	24.8	1540
FG16M161X185	185	1	0.106	27.2	1900
FG16M161X240	240	1	0.0801	30.4	2410
FG16M161X300	300	1	0.0641	33	3031
FG16M161X500	500	1	0.0384	39	4900
FG16M161X630	6300	1	0.0287	43.4	6257

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.