

Light Duty V75 PVC Flexible Cord 250/250V Cable - 0.50mm² to 0.75mm²



Description

Light Duty V75 PVC Flexible Cords are designed as electrical supply cables for a wide range of domestic and commercial light appliances to 250V including radios, shavers, desk lamps, and small office machinery under Australian and New Zealand Standards. This cable features plain annealed flexible stranded copper conductors, insulated and jacketed with a Polyvinyl Chloride (PVC) compound specifically formulated to handle continuous operating temperatures up to 75°C. Manufactured in both flat and round configurations, the range fully complies with the structural requirements of AS/NZS 3191 and AS/NZS 1125 standards, making them an ideal choice for double-insulated appliances or equipment requiring a dependable earth connection.

These cables are suitable for installation in internal, dry environments only where there is no risk of moisture or atmospheric exposure. Due to their light-duty construction, they offer minimal resistance against physical damage and are not advised for outdoor use or demanding commercial areas. The flexible PVC outer sheath is intended purely for low-stress setups and must not be installed where it will encounter mechanical strain, severe abrasion, crushing forces, or direct impact.

For safe installation, the cable must be handled carefully to prevent tight kinks, maintaining a minimum bending radius of six times the overall cable diameter during flexing. Installers should always use appropriate protective bushings or cord grip fittings when feeding the cable through enclosures or equipment chassis to eliminate any potential for structural chafing. As these are designated as flexible cords, standard electrical safety regulations require that they only be used to connect temporary or portable equipment and must never be utilized as a permanent substitute for the fixed wiring within a building structure.

Key Features



Voltage Rating
250 Volts



Minimum Bending Radius
Fixed: 6 x overall diameter



Temperature Limits
Maximum operating temperature: +75°C

Core Colours

2 Cores - Brown, Blue

3 Cores - Brown, Blue, Green Yellow

Sheath Colours:

Grey White Black Orange

Standards

- AS/NZS 1125
- AS/NZS 3191

Construction

- **Conductor:** Stranded copper conductor
- **Insulation:** Polyvinyl Chloride (PVC)
- **Outer Sheath:** Polyvinyl Chloride (PVC)
- **Sheath Colour:** Black, Grey, White or Orange

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

Light Duty V75 PVC Flexible Cord 250/250V Cable - 0.50mm² to 0.75mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Insulation Thickness (mm)	Sheath Thickness (mm)	Overall Diameter(mm)	Weight(Kg/Km)
V75LIGHT2X/5	0.50	2	0.50	0.60	5.20	3.70
V75LIGHT3X/5	0.50	3	0.50	0.60	5.50	4.30
V75LIGHT2X/75	0.75	2	0.50	0.60	5.70	4.60
V75LIGHT3X/75	0.75	3	0.50	0.60	5.90	5.40

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.