


Legrand Tray - MRFB 90° Bends PG



Description

Legrand Tray - MRFB 90° Bends PG

Legrand Swifts Cable Tray is used to guide and support insulated cables used for power distribution, control, and communication it is an effective way to manage cable in commercial and industrial construction.

The perforated design allows installers the ultimate flexibility and quick installation, allowing cables to be pulled through the slots but also allowing for air circulation, water drainage.

Medium duty return flange tray – MRF

Depth – 25mm

PG – Pre-galvanised to BS EN 10346:2009

Key Features

Standards

Construction

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance



Legrand Tray - MRFB 90° Bends PG - Dimensions

Reference
MRFB/

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.