


MV Aerial Bundle Cable (ABC) Unscreened 12.7/22kV - 35mm² to 185mm²



Description

Aerial bundled cables (ABC) are designed for overhead power distribution, specifically for low voltage applications. They offer a higher safety level, reduced maintenance, and lower power losses compared to bare conductors. ABC cables are commonly used in rural areas or urban locations where burying cables is not feasible.

Key Features



Voltage Rating
12.7/22 (24)kV



Minimum Bending Radius
12 x Overall Diameter



Temperature Limits
Maximum operating temperature: +90°C

Standards

- BS 2627
- AS/NZS 3599-2
- IEC 60502
- IEC 60228

Construction

- **Conductor:** Class 2 Stranded Aluminium Conductor
- **Conductor Screen:** Extruded semi-conductive screen
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Extruded semi-conductive screen
- **Water Blocking:** Semi-conductive swellable tape
- **Outer Sheath:** High Density Polyethylene (HDPE)
- **Sheath Colour:** Black
- **Support Conductor:** Galvanised Steel Wires

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

MV Aerial Bundle Cable (ABC) Unscreened 12.7/22kV - 35mm² to 185mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Insulation Thickness (mm)	Sheath Thickness (mm)	Overall Dimensions(mm)
22KVABC3X35	35	3	5.5	1.2	61.0
22KVABC3X50	50	3	5.5	1.2	63.5
22KVABC3X70	70	3	5.5	1.2	67.0
22KVABC3X95	95	3	5.5	1.2	70.0
22KVABC3X120	120	3	5.5	1.2	76.0
22KVABC3X150	150	3	5.5	1.2	79.0
22KVABC3X185	185	3	5.5	1.2	82.0

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.