


## MV IEC 60502-2 Screened Aerial Bundle Cable (ABC) 19/33kV



### Description

Aerial bundled cables (ABC) are designed for overhead power distribution, specifically for low voltage applications. They offer a higher safety level, reduced maintenance, and lower power losses compared to bare conductors. ABC cables are commonly used in rural areas or urban locations where burying cables is not feasible.

### Key Features



**Voltage Rating**  
19/33 (36)kV



**Minimum Bending Radius**  
15 x Overall Diameter



**Temperature Limits**  
Maximum operating temperature: +90°C

### Standards

- AS/NZS 3599-1
- IEC 60502-2
- IEC 60228

### Construction

- **Phase Conductor:** Class 2 Stranded Aluminium
- **Conductor Screen:** Extruded semi-conductive screen
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Extruded semi-conductive screen
- **Metallic Screen:** Copper wires or copper tape screen
- **Waterblocking Tape:** Semi-conductive swellable tape
- **Outer Sheath:** High Density Polyethylene (HDPE)
- **Sheath Colour:** Black
- **Support Conductor:** Galvanised Steel Wires

### QA Lab

#### Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



### Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

### ecovadis

MV IEC 60502-2 Screened Aerial Bundle Cable (ABC) 19/33kV - Dimensions

Reference	Conductor Size (mm2)	No Of Cores	Insulation Thickness (mm)	Sheath Thickness (mm)	Overall Dimensions(mm)
33KVABCHDSCR3X50	50	3	8.0	2.0	70.0
33KVABCHDSCR3X70	70	3	8.0	2.0	68.5
33KVABCHDSCR3X95	95	3	8.2	2.1	74.5
33KVABCHDSCR3X120	120	3	8.2	2.1	80.0
33KVABCHDSCR3X150	150	3	8.4	2.2	82.0
33KVABCHDSCR3X185	185	3	8.5	2.2	86.0

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.