

## N2XSE(F)H 24kV Power Cable



### Description

Medium voltage power cables for fixed installations in distribution networks and for connection to process machinery, Plant and to power generation equipment. Cables can be fixed on cable trays, within conduits or fixed to walls. This cable is not suitable for direct burial.

### Key Features



**Voltage Rating**  
12/20 (24kV)



**Minimum Bending Radius**  
10 x Overall Diameter



**Flame Retardancy**  
BS EN/IEC 60332-1-2



**Temperature Limits**  
Temperature Range: -5°C to +90°C

### Standards

- UV Resistant Sheath
- IEC 60502-02
- BS EN/IEC 60332-1-2
- BS EN/IEC 60228

### Construction

- **Conductor:** Class 2 stranded copper
- **Conductor Screen:** Bonded semi conductive material
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Strippable Extruded Semi Conductor
- **Metallic Screen:** Copper Wires plus Copper tape
- **Outer Sheath:** Low Smoke Zero Halogen (LSZH)
- **Sheath Colour:** Red or Black

### QA Lab

#### Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



### Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

### ecovadis

N2XSE(F)H 24kV Power Cable - Dimensions

| Reference        | Conductor Size (mm2) | No Of Cores | Overall Diameter(mm) | Weight(Kg/Km) |
|------------------|----------------------|-------------|----------------------|---------------|
| 22KVN2XSEFH3X35  | 35                   | 3           | 52                   | 3200          |
| 22KVN2XSEFH3X50  | 50                   | 3           | 55                   | 3800          |
| 22KVN2XSEFH3X70  | 70                   | 3           | 60                   | 4800          |
| 22KVN2XSEFH3X95  | 95                   | 3           | 63                   | 5750          |
| 22KVN2XSEFH3X120 | 120                  | 3           | 66                   | 6650          |
| 22KVN2XSEFH3X150 | 150                  | 3           | 70                   | 8000          |
| 22KVN2XSEFH3X185 | 185                  | 3           | 73                   | 9100          |
| 22KVN2XSEFH3X240 | 240                  | 3           | 80                   | 11200         |
| 22KVN2XSEFH3X300 | 300                  | 3           | 84                   | 11350         |
| 22KVN2XSEFH3X400 | 400                  | 3           | 90                   | 16320         |

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

