

N2XS(FL)2Y 6/10 (12)kV Cable - 50mm² to 630mm²

Description

Medium voltage MDPE power cables for distribution networks. This cable is used extensively in the renewables and datacentre sectors. N2XS(FL)2Y cable is suitable for external installation. Cables can be fixed on cable trays, within conduits or fixed to walls and is suitable for burial in ducts. The cable has a UV Resistant outer sheath and three water blocking layers to make it water resistant

Key Features



Voltage Rating
6/10 (12)kV



Minimum Bending Radius
15 x Overall Diameter



Temperature Limits
Temperature Range: -20°C to +60°C
Conductor Operating Temperature: +90°C
Short Circuit Temperature up to 5 sec: 250°C

Standards

- IEC 60332-1-2
- IEC 60502-2
- IEC 60228
- UV Resistant: ISO 4892-3
- BS EN 60332-1-2
- VDE 0276-620
- HD 620

Construction

- **Conductor:** Class 2 stranded copper conductor
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Semi-Conductive XLPE
- **Longitudinal Waterblocking:** Semi-conductive swellable tape
- **Screen:** Copper wires and copper tape
- **Water Blocking:** Al/PET (Aluminium/Polyester) Tape bonded to sheath
- **Longitudinal Water Blocking:** Swellable tapes
- **Outer Sheath:** Medium Density Polyethylene (MDPE)
- **Sheath Colour:** Red or Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

N2XS(FL)2Y 6/10 (12)kV Cable - 50mm² to 630mm² - Dimensions

Reference	Conductor Size (mm2)	Nominal Conductor Diameter	Insulation Thickness (mm)	CWS(mm)	Sheath Thickness (mm)	Overall Diameter(mm)	Weight(Kg/Km)
12KVN2XS(FL)2Y1 X50	50	83	2.75	RM/16	1.8	23.5	975
12KVN2XS(FL)2Y1 X70	70	10.0	2.75	RM/16	1.8	25.5	1195
12KVN2XS(FL)2Y1 X95	95	11.5	3.0	RM/16	1.8	26.0	1495
12KVN2XS(FL)2Y1 X120	120	13.0	3.0	RM/16	1.85	28.0	1800
12KVN2XS(FL)2Y1 X150	150	14.5	3.25	RM/25	1.9	30.0	2220

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.