

N2XSYPVC 8.7/15 (17.5) kV Cable - 25mm² to 630mm²



Description

Medium voltage XLPE / PVC power cables for distribution networks. This cable is used extensively in the renewables and datacentre sectors. N2XSYP cable is suitable for external installation. Cables can be fixed on cable trays, within conduits or fixed to walls and is suitable for burial in ducts where there is no danger of water ingress. The cable has a UV Resistant outer sheath

Key Features



Voltage Rating
8.7/15 (18) kV



Minimum Bending Radius
15 x Overall Diameter



Oils, Greases and Chemicals Resistant
Yes



Flame Retardancy
BS EN 60332-1-2



Temperature Limits
Temperature Range: -15°C to +90°C

Standards

- IEC 60502-2
- IEC 60228
- BS EN/IEC 60332-1-2

Construction

- **Conductor:** Class 2 stranded copper conductor
- **Conductor Screen:** Semi-Conductive material
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Semi conducting compound
- **Metallic Screen:** Copper Wires plus Copper tape
- **Separator:** Polyester Tape
- **Outer Sheath:** Polyvinyl Chloride (PVC)
- **Sheath Colour:** Red

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

N2XSY XLPE PVC 8.7/15 (17.5) kV Cable - 25mm² to 630mm² - Dimensions

Reference	Conductor Size (mm2)	Insulation Thickness (mm)	Sheath Thickness (mm)	Nominal Conductor Diameter	CWS(mm)	Overall Diameter(mm)	Weight(Kg/Km)
8/15N2XSY1X25	25	4.0	1.6	6.0	RM/16	22.5	650
8/15N2XSY1X35	35	4.0	1.6	7.0	RM/16	23.0	755
8/15N2XSY1X50	50	4.0	1.7	8.4	RM/16	24.0	895
8/15N2XSY1X70	70	4.0	1.8	10.0	RM/16	25.5	1100
8/15N2XSY1X95	95	4.0	1.8	11.5	RM/16	27.5	1375
8/15N2XSY1X120	120	4.5	2.0	13.0	RM/25	29.0	1635
8/15N2XSY1X150	150	4.5	2.0	15.0	RM/25	30.5	1895
8/15N2XSY1X185	185	4.5	2.2	16.5	RM/25	32.5	2270
8/15N2XSY1X240	240	4.5	2.2	18.5	RM/25	35.0	3150
8/15N2XSY1X300	300	4.5	2.4	20.5	RM/25	38.0	3465
8/15N2XSY1X400	400	5.0	2.5	24.0	RM/35	41.0	4350
8/15N2XSY1X500	500	5.0	2.6	28.0	RM/35	45.0	5825
8/15N2XSY1X630	630	5.0	2.7	32.0	RM/35	48.0	6855

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

