NA2XS2Y XLPE MDPE 8.7/15 (17.5) kV Cable - 50mm² to 1000mm²



Description

Medium voltage power cables with aluminium Conductor for distribution networks. This cable is used extensively in the renewables and datacentre sectors. NA2XS2Y cable is suitable for external installation. Cables can be fixed on cable trays, within conduits or fixed to walls and is suitable for burial in ducts. The cable has a UV Resistant outer sheath.

Key Features

Voltage Rating
8.7/15 (18) kV

Minimum Bending Radius
15 x Overall Diameter

Temperature Limits
Temperature Range: -20°C to +60°C
Conductor Operating Temperature: +90°C
Short Circuit Temperature up to 5 sec: 250°C

Standards

- IEC 60332-1-2
- IEC 60502-2
- IEC 60228
- BS EN 60332-1-2

Construction

- **Conductor**: Class 2 Stranded Aluminium Conductor
- **Conductor Screen**: Semi-Conductive material
- **Insulation**: Cross Linked polyethylene (XLPE)
- **Insulation Screen**: Semi-Conductive XLPE
- **Metallic Screen**: Copper Wires plus Copper tape
- **Separator**: Polyester Tape
- **Outer Sheath**: Medium Density Polyethylene (MDPE)
- **Sheath Colour**: Red

Training & Testing Lab

AN ISO/IEC 17025 ACCREDITED FACILITY

Cleveland Cable Test & Training Lab
Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing.

ISO/IEC 17025 Accredited Testing Laboratory

CPR
Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.

Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.

ecovadis
Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

NA2XS2Y XLPE MDPE 8.7/15 (17.5) kV Cable - 50mm² to 1000mm² - Dimensions

Reference	Conductor Size (mm2)	Nominal Conductor Diameter	Insulation Thickness (mm)	CWS(mm)	Sheath Thickness (mm)	Overall Diameter(mm)	Weight(Kg/Km)
8/15NA2XS2Y1X50	50	8.5	4.2	RM/16	1.7	27.5	820
8/15NA2XS2Y1X70	70	10.0	4.2	RM/16	1.8	29.0	975
8/15NA2XS2Y1X95	95	11.5	4.2	RM/25	1.8	30.5	1185
8/15NA2XS2Y1X120	120	13.0	4.2	RM/35	2.0	32.0	1430
8/15NA2XS2Y1X150	150	14.5	4.2	RM/35	2.0	33.5	1550
8/15NA2XS2Y1X185	185	16.0	4.4	RM/35	2.2	35.0	1695
8/15NA2XS2Y1X240	240	17.4	4.4	RM/35	2.4	37.4	1915
8/15NA2XS2Y1X300	300	20.6	4.5	RM/50	2.4	39.3	2125
8/15NA2XS2Y1X400	400	23.0	4.5	RM/50	2.6	42.3	2445

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.