

NA2XS(FL)2Y 6/10 (12)kV Cable - 50mm² to 630mm²



Description

Medium voltage power cables with aluminium Conductor for distribution networks. This cable is used extensively in the renewables and datacentre sectors. NA2XS(FL)2Y cable is suitable for external installation. Cables can be fixed on cable trays, within conduits or fixed to walls and is suitable for burial in ducts. The cable has two longitudinal waterblocking layers and a radial waterblocking aluminium tape which is bonded to a UV Resistant MDPE outer sheath.

Key Features



Voltage Rating
6/10 (12)kV



Minimum Bending Radius
15 x Overall Diameter



Flame Retardancy
BS EN/IEC 60332-1-2



Temperature Limits
Temperature Range: -20°C to +60°C
Conductor Operating Temperature: +90°C
Short Circuit Temperature up to 5 sec: 250°C

Standards

- BS EN 60332-1-2
- UV Resistant: ISO 4892-3
- IEC 60228
- IEC 60502-2

Construction

- **Conductor:** Class 2 Stranded Aluminium Conductor
- **Conductor Screen:** Semi-Conductive material
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Semi-conductive material (bonded)
- **Longitudinal Waterblocking:** Swellable tapes
- **Metallic Screen:** Copper Wires plus Copper tape
- **Waterblocking Tape:** Al/PET (Aluminium/Polyester) Tape bonded to sheath
- **Outer Sheath:** Medium Density Polyethylene (MDPE)
- **Sheath Colour:** Red or Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance



NA2XS(FL)2Y 6/10 (12)kV Cable - 50mm² to 630mm² - Dimensions

Reference	Conductor Size (mm2)	Insulation Thickness (mm)	Sheath Thickness (mm)	Nominal Conductor Diameter	CWS(mm)	Overall Diameter(mm)	Weight(Kg/Km)
6/10NA2XS(FL)2Y1 X50	50	3.0	1.6	8.5	RM/16	23.0	595
6/10NA2XS(FL)2Y1 X70	70	3.2	1.7	10.0	RM/16	34.5	695
6/10NA2XS(FL)2Y1 X95	95	3.4	1.7	11.5	RM/16	26.0	810
6/10NA2XS(FL)2Y1 X120	120	3.4	1.8	13.0	RM/16	27.5	925
6/10NA2XS(FL)2Y1 X150	150	3.5	1.9	14.5	RM/25	29.0	1175
6/10NA2XS(FL)2Y1 X185	185	3.5	1.9	16.0	RM/25	31.5	1275
6/10NA2XS(FL)2Y1 X240	240	3.5	2.0	18.5	RM/25	33.5	1475
6/10NA2XS(FL)2Y1 X300	300	3.5	2.2	21.0	RM/25	37.0	1675
6/10NA2XS(FL)2Y1 X400	400	4.0	2.2	23.5	RM/35	39.5	2085
6/10NA2XS(FL)2Y1 X500	500	4.0	2.4	27.0	RM/35	43.0	2595
6/10NA2XS(FL)2Y1 X630	630	4.0	2.5	30.5	RM/35	46.5	3120

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

