

Nexans - BS7835 Single Core Armoured Mains Cable CU XLPE AWA LSZH 8.7/15kV - 50mm² to 500mm²



Description

BS7835 cables from Nexans are armoured power cables designed for medium voltage fixed installations, such as power networks, industrial installations, power supply stations and substations. They can be installed indoors, outdoors, underground and in cable ducts. These single core cables have copper conductors with cross-linked polyethylene (XLPE) insulation, various screen options, water blocking options, aluminium wire armour and LSZH bedding and outer sheath.

The UV resistant LSZH outer sheath makes the cable suitable for internal use in buildings, power stations and switchboards, where it is often installed on cable tray for industrial applications. Nexans BS7835 cables can also be used externally in cable ducts and, due to the armour, can be buried directly in free-draining soil.

Key Features



Voltage Rating
8.7/15 (17.5) kV



Minimum Bending Radius
15 x Overall Diameter



Flame Retardancy
BS EN/IEC 60332-1-2
BS EN/IEC 60332-3-24



Temperature Limits
Conductor Maximum Operating Temperature: +90°C
Maximum Short Circuit Temperature: +250°C

Core Colours

Outer Sheath: Red or Black

Standards

Construction

- **Conductor:** Class 2 Copper Conductor
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Semi-Conductive XLPE
- **Metallic Screen:** Individual copper tape screen
- **Filler:** Polyethylene Terephthalate (PET) fibres
- **Bedding:** Low Smoke Zero Halogen (LSZH)
- **Armour:** Aluminium Wire Armour (AWA)
- **Outer Sheath:** Low Smoke Zero Halogen (LSZH)

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

Nexans - BS7835 Single Core Armoured Mains Cable CU XLPE AWA LSZH 8.7/15kV - 50mm² to 500mm² - Dimensions

Reference	Conductor Size (mm2)	No Of Cores	Sheath Thickness (mm)	Overall Diameter(mm)	Weight(Kg/Km)
15KVXLPE1X50	50	1	1.33	29.0	1300
15KVXLPE1X70	70	1	1.40	31.0	1600
15KVXLPE1X95	95	1	1.47	33.5	2000
15KVXLPE1X120	120	1	1.55	35.0	2265
15KVXLPE1X150	150	1	1.58	37.5	2625
15KVXLPE1X185	185	1	1.62	39.5	3000
15KVXLPE1X240	240	1	1.65	42.5	3550
15KVXLPE1X300	300	1	1.75	45.0	4500
15KVXLPE1X400	400	1	1.8	48.5	5450
15KVXLPE1X500	500	1	1.9	51.0	6500

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.