

Nexans - N2XS2Y CU MDPE 18/30 (36)kV Cable - 50mm² to 630mm²

Description

Medium voltage power cables for distribution networks. This cable is used extensively in the renewables and datacentre sectors. From Nexans, the N2XS2Y cable is suitable for external installation. Cables can be fixed on cable trays, within conduits or fixed to walls and are suitable for burial in ducts. The cable has a UV resistant outer sheath.

Key Features



Voltage Rating
18/30 (36)kV



Minimum Bending Radius
15 x Overall Diameter



Temperature Limits
 Temperature Range: -20°C to +60°C
 Conductor Operating Temperature: +90°C
 Short Circuit Temperature up to 5 sec: 250°C

Standards

- IEC 60332-1-2
- IEC 60502-2
- IEC 60228
- UV Resistant: ISO 4892-3
- BS EN 60332-1-2
- VDE 0276-620
- HD 620

Construction

- **Conductor:** Class 2 stranded copper conductor
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Semi conducting compound
- **Screen:** Copper Tape Screen (CTS)
- **Outer Sheath:** Medium Density Polyethylene (MDPE)
- **Sheath Colour:** Red or Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

Nexans - N2XS2Y CU MDPE 18/30 (36)kV Cable - 50mm² to 630mm² - Dimensions

Reference	Conductor Size (mm2)	Nominal Conductor Diameter	Insulation Thickness (mm)	CWS(mm)	Sheath Thickness (mm)	Overall Diameter(mm)	Weight(Kg/Km)
18/30N2XSFL2Y1X 50	50	8.2	7.00	RM/16	1.9	31.8	1240
18/30N2XSFL2Y1X 70	70	9.9	7.00	RM/16	2.0	32.9	1550
18/30N2XSFL2Y1X 95	95	11.6	7.00	RM/16	2.1	35.1	1900
18/30N2XSFL2Y1X 120	120	13.0	7.00	RM/16	2.15	36.3	2150
18/30N2XSFL2Y1X 150	150	14.6	7.00	RM/25	2.2	38.2	2620
18/30N2XSFL2Y1X 185	185	16.0	7.00	RM/25	2.3	39.8	2975
18/30N2XSFL2Y1X 240	240	18.8	7.10	RM/25	2.3	43.1	3800
18/30N2XSFL2Y1X 300	300	20.8	7.10	RM/25	2.4	45.4	4250
18/30N2XSFL2Y1X 400	400	23.2	7.10	RM/35	2.5	48.4	5350
18/30N2XSFL2Y1X 500	500	26.4	7.10	RM/35	2.6	51.3	6200
18/30N2XSFL2Y1X 630	630	30.3	7.10	RM/35	2.7	56.4	7600

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.