

Nexans - N2XS(F)H 6/10 (12)kV Cable - 50mm² to 630mm²

Description

LSZH medium voltage power cables for distribution networks. This cable is used extensively in the renewables and datacentre sectors. N2XS(F)H cable is suitable for external installation and is supplied by Nexans. Cables can be fixed on cable trays, within conduits or fixed to walls and are suitable for burial in ducts. The cable has a UV resistant outer sheath and 2 water blocking layers.

Key Features



Voltage Rating
8.7/15 (18) kV



Minimum Bending Radius
15 x Overall Diameter

Standards

- Acid Gas Emission to IEC 60754-1, IEC 60754-2
- BS EN 60332-1-2
- UV Resistant: ISO 4892-3
- IEC 60228
- IEC 60502-2
- IEC 60332-1-2

Construction

- **Conductor:** Class 2 stranded copper conductor
- **Conductor Screen:** Semi-Conductive material
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Semi-Conductive XLPE
- **Longitudinal Waterblocking:** Semi-conductive swellable tape
- **Longitudinal Water Blocking:** Swellable tapes
- **Sheath:** Low Smoke Zero Halogen (LSZH)
- **Outer Sheath:** Low Smoke Zero Halogen (LSZH)
- **Sheath Colour:** Red or Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

Nexans - N2XS(F)H 6/10 (12)kV Cable - 50mm² to 630mm² - Dimensions

Reference	Conductor Size (mm2)	Nominal Conductor Diameter	Insulation Thickness (mm)	CWS(mm)	Sheath Thickness (mm)	Overall Diameter(mm)	Weight(Kg/Km)
6/10N2XSFH1X50	50	8.25	3.2	RM/16	1.65	22.5	920
6/10N2XSFH1X70	70	9.75	3.2	RM/16	1.65	24.5	1195
6/10N2XSFHH1X95	95	11.50	3.2	RM/16	1.75	26.5	1400
6/10N2XSFHH1X120	120	13.0	3.3	RM/16	1.75	27.5	1750
6/10N2XSFHH1X150	150	14.9	3.3	RM/25	1.8	29.5	2195
6/10N2XSFHH1X185	185	16.5	3.3	RM/25	1.85	31.0	2425
6/10N2XSFHH1X240	240	19.0	3.4	RM/25	1.95	34.0	3195
6/10N2XSFHH1X300	300	21.0	3.4	RM/25	2.0	36.5	3595
6/10N2XSFH1X400	400	24.0	3.4	RM/35	2.15	39.5	4750
6/10N2XSFH1X500	500	27.0	3.5	RM/35	2.25	42.5	5820
6/10N2XSFH1X630	630	30.5	3.5	RM/35	2.35	46.0	6995

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.