Nexans - NA2XS(F)H 18/30 (36)kV Cable - 50mm² to 630mm²

Description

Medium voltage power cables with aluminium conductor for distribution networks. This cable is used extensively in the renewables and datacentre sectors. NA2XS(F)H cable from Nexans is suitable for external installation. Cables can be fixed on cable trays, within conduits or fixed to walls and are suitable for burial in ducts. The cable has two waterblocking layers and a UV resistant Low Smoke, Zero Halogen (LSZH) outer sheath.

Key Features

Voltage Rating
18/30 (36)kV

Minimum Bending Radius
15 x Overall Diameter

Flame Retardancy
BS EN/IEC 60332-1-2
BS EN/IEC 60332-3-24

Temperature Limits
Temperature Range: -20°C to +60°C
Conductor Operating Temperature: +90°C
Short Circuit Temperature up to 5 sec: 250°C

Standards

- IEC 60502-2
- IEC 60228
- UV Resistant: EN 50396

Construction

- **Conductor**: Class 2 Stranded Aluminium Conductor
- **Conductor Screen**: Semi-Conductive material
- **Insulation**: Cross Linked polyethylene (XLPE)
- **Insulation Screen**: Semi-conductive material (bonded)
- **Longditudinal Waterblocking**: Semi-conductive swellable tape
- **Metallic Screen**: Copper Wires plus Copper tape
- **Tape**: Longditudinal Water Blocking Tape
- **Outer Sheath**: Low Smoke Zero Halogen (LSZH)
- **Sheath Colour**: Red or Black

Training & Testing Lab

AN ISO/IEC 17025 ACCREDITED FACILITY

Cleveland Cable Test & Training Lab
Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing.

ISO/IEC 17025 Accredited Testing Laboratory

CPR
Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.

Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.

ecovadis
Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

Nexans - NA2XS(F)H 18/30 (36)kV Cable - 50mm² to 630mm² - Dimensions

Reference	Conductor Size (mm2)	Nominal Conductor Diameter	Insulation Thickness (mm)	CWS(mm)	Sheath Thickness (mm)	Overall Diameter(mm)	Weight(Kg/Km)
18/30NA2XS(F)H1X 50	50	8.5	7.5	RM/16	1.8	32.5	1025
18/30NA2XS(F)H1X 70	70	10.0	7.5	RM/16	1.9	34.0	1125
18/30NA2XS(F)H1X 95	95	11.5	7.5	RM/16	1.9	35.5	1340
18/30NA2XS(F)H1X 120	120	13.0	7.5	RM/16	2.0	37.0	1440
18/30NA2XS(F)H1X 150	150	14.5	8.0	RM/25	2.0	39.5	1645
18/30NA2XS(F)H1X 185	185	16.0	8.0	RM/25	2.2	41.5	1850
18/30NA2XS(F)H1X 240	240	18.5	8.0	RM/25	2.3	43.0	2055
18/30NA2XS(F)H1X 300	300	21.0	8.5	RM/25	2.4	46.0	2295
18/30NA2XS(F)H1X 400	400	23.0	8.5	RM/35	2.4	49.5	2795
18/30NA2XS(F)H1X 500	500	26.2	8.5	RM/35	2.6	52.2	3325
18/30NA2XS(F)H1X 630	630	30.5	8.5	RM/35	2.8	56.4	3835

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

31196