

Nexans - NA2XSH 18/30 (36)kV Cable - 50mm² to 630mm²



Description

UV resistant medium voltage cables for distribution networks, as well as for connection to generation units and plant and process equipment. The LSZH outer sheath allows for internal and external installation, including directly in the ground and in cable ducts. Supplied by Nexans.

Key Features



Voltage Rating
18/30 (36)kV



Minimum Bending Radius
15 x Overall Diameter



Flame Retardancy
BS EN/IEC 60332-1-2



Temperature Limits
Temperature Range: -20°C to +60°C
Conductor Operating Temperature: +90°C
Short Circuit Temperature up to 5 sec: 250°C

Standards

- IEC/EN 60754-1/2
- BS EN/IEC 60332-1-2
- IEC/EN 61034-1/2,
- IEC 60228
- IEC 60502-2

Construction

- **Conductor:** Class 2 Stranded Aluminium Conductor
- **Conductor Screen:** Semi-Conductive material
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Semi-Conductive XLPE
- **Filler:** LSZH (Low Smoke Zero Halogen)
- **Metallic Screen:** Copper Wires plus Copper tape
- **Outer Sheath:** Low Smoke Zero Halogen (LSZH)
- **Sheath Colour:** Red

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

Nexans - NA2XSH 18/30 (36)kV Cable - 50mm² to 630mm² - Dimensions

Reference	Conductor Size (mm2)	Nominal Conductor Diameter	Insulation Thickness (mm)	CWS(mm)	Sheath Thickness (mm)	Overall Diameter(mm)	Weight(Kg/Km)
18/30NA2XS1X50	50	8.5	7.6	RM/16	1.8	32.5	950
18/30NA2XS1X70	70	10.0	7.6	RM/16	1.8	33.5	1155
18/30NA2XS1X95	95	11.5	7.8	RM/16	2.0	35.0	1260
18/30NA2XS1X120	120	13.0	7.8	RM/16	2.0	36.5	1370
18/30NA2XS1X150	150	14.5	8.0	RM/25	2.2	39.0	1570
18/30NA2XS1X185	185	16.0	8.0	RM/25	2.2	41.0	1775
18/30NA2XS1X240	240	18.5	8.0	RM/25	2.4	43.5	1975
18/30NA2XS1X300	300	21.0	8.0	RM/25	2.5	46.0	2330
18/30NA2XS1X400	400	24.0	8.0	RM/35	2.6	48.5	2840
18/30NA2XS1X500	500	26.5	8.5	RM/35	2.7	52.0	3095
18/30NA2XS1X630	630	31.0	8.5	RM/35	2.8	57.0	3595

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.