

Nexans - NA2XSH XLPE LSZH 8.7/15 (17.5) kV Cable - 50mm² to 1000mm²



Description

Medium voltage power cables with aluminium conductor for distribution networks. This cable is used extensively in the renewables and datacentre sectors. NA2XSH cable from Nexans is suitable for external installation. Cables can be fixed on cable trays, within conduits or fixed to walls and are suitable for burial in ducts. The cable has a Low Smoke Zero Halogen UV resistant outer sheath.

Key Features



Voltage Rating
8.7/15 (18) kV



Minimum Bending Radius
15 x Overall Diameter



Flame Retardancy
BS EN/IEC 60332-1-2



Temperature Limits
Temperature Range: -20°C to +60°C
Conductor Operating Temperature: +90°C
Short Circuit Temperature up to 5 sec: 250°C

Standards

- IEC/EN 60754-1/2
- BS EN/IEC 60332-1-2
- IEC 61034-2
- IEC 60228
- IEC 60502-2

Construction

- **Conductor:** Class 2 Stranded Aluminium Conductor
- **Conductor Screen:** Semi-Conductive material
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Semi-Conductive XLPE
- **Overall Tape Screen:** Non swelling semi conductive tape
- **Metallic Screen:** Copper Wires plus Copper tape
- **Tape:** Polyester tape wrapping
- **Outer Sheath:** Low Smoke Zero Halogen (LSZH)
- **Sheath Colour:** Red

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

Nexans - NA2XSH XLPE LSZH 8.7/15 (17.5) kV Cable - 50mm² to 1000mm² - Dimensions

Reference	Conductor Size (mm2)	Nominal Conductor Diameter	Insulation Thickness (mm)	CWS(mm)	Sheath Thickness (mm)	Overall Diameter(mm)	Weight(Kg/Km)
8/15NA2XS1X50	50	8.5	4.0	RM/16	1.8	27.5	825
8/15NA2XS1X70	70	10.0	4.0	RM/25	1.8	29.0	995
8/15NA2XS1X95	95	11.2	4.0	RM/35	1.8	30.5	1210
8/15NA2XS1X120	120	13.0	4.0	RM/50	1.9	32.0	1455
8/15NA2XS1X150	150	14.5	4.5	RM/50	1.9	33.5	1585
8/15NA2XS1X185	185	16.5	4.5	RM/50	2.0	35.0	1735
8/15NA2XS1X240	240	18.5	4.5	RM/50	2.2	37.5	1935
8/15NA2XS1X300	300	20.5	4.5	RM/50	2.2	39.5	2150
8/15NA2XS1X400	400	23.5	4.5	RM/50	2.4	42.0	2465
8/15NA2XS1X500	500	26.5	4.5	RM/50	2.4	45.5	2880
8/15NA2XS1X630	630	30.0	5.0	RM/50	2.6	50.5	3380
8/15NA2XS1X800	800	33.5	5.0	RM/50	2.8	54.0	4005
8/15NA2XS1X1000	1000	39	5.0	RM/50	2.8	60.0	4775

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.