

(N)TMCGCWÖU8,7/15 (17.5kV)



(N)TMCGCWÖU cable is Medium voltage, class 5 single core cable with added semiconductive material between each of the Core, the insulation and the earth conductor and surrounded with a rubber outer sheath. It is usually used for short-length connections of transformers and switchgear, as well as power cables on mining equipment and alongside conveyor belts.

(N)TMCGCWÖU comes in 8 different power ranges. from 3.6/6kV to 26/45kV

Key Features



Voltage Rating
8.7/15 (18) kV



Minimum Bending Radius
Fixed: 6 x overall diameter



Oils, Greases and Chemicals Resistant
Yes



UV/Ozone Resistance
Yes



Flame Retardancy
IEC/EN 60332-1-2



Temperature Limits
Fixed: -50°C to +90°C

Construction

- **Conductor:** Tinned copper conductor
- **Conductor Screen:** Semi-Conductive material
- **Insulation:** Quality Rubber Compound, according to VDE 0207 Part 20
- **Insulation Screen:** Inner and outer semi-conductive rubber layer on the insulation
- **Concentric Conductor:** Copper wires with counter helix of copper tape
- **Outer Sheath:** Quality rubber compound, according to VDE 0207 part 21
- **Sheath Colour:** Red

Standards

- IEC 60228
- BS EN/IEC 60332-1-2
- VDE 0250 PT812
- VDE 0295
- UV Resistant: ISO 4892-2
- Oil resistant: IEC 60811-404
- Ozone resistant: IEC 60811-403

(N)TMCGCWÖU8,7/15 (17.5kV) - Dimensions

Reference	Conductor Size (mm2)	Nominal Conductor Diameter	CWS(mm)	Max Overall Dia	Max Bending Radius (mm)	Weight(Kg/Km)
17KV(N)TMCGC WÖU1X25	25	6.8	RM/16	23.1	139	820
17KV(N)TMCGC WÖU1X35	35	7.8	RM/16	24.0	144	930
17KV(N)TMCGC WÖU1X50	50	9.4	RM/16	25.5	153	1110
17KV(N)TMCGC WÖU1X70	70	11.2	RM/16	27.9	168	1370
17KV(N)TMCGC WÖU1X95	95	12.7	RM/16	29.5	177	1620
17KV(N)TMCGC WÖU1X120	120	14.4	RM/16	31.4	189	1910
17KV(N)TMCGC WÖU1X150	150	16.3	RM/25	34.8	209	2430
17KV(N)TMCGC WÖU1X185	185	17.6	RM/25	35.8	215	2720
17KV(N)TMCGC WÖU1X240	240	20.6	RM/25	39.8	239	3450
17KV(N)TMCGC WÖU1X300	300	22.7	RM/25	41.7	251	3860
17KV(N)TMCGC WÖU1X400	400	25.2	RM/35	44.9	270	4850
17KV(N)TMCGC WÖU1X500	500	29.5	RM/35	49.5	297	6150
17KV(N)TMCGC WÖU1X630	630	34.0	RM/35	55.0	330	8070

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

For more information contact: 01642 241 133

