

PAS5308 Part2, Type1 Instrumentation Cable, Individually Screened - 0.5mm² to 1.5mm²



Description

Manufactured to PAS5308, instrumentation cables are intrinsically safe and designed for use in communication and instrumentation applications in and around process industries for transmission of signals in control systems. The signals can be analogue or digital from a variety of sensors and transducers.

Key Features



Voltage Rating
300/500 Volts



Minimum Bending Radius
Fixed: 6 x overall diameter



Flame Retardancy
BS EN/IEC 60332-1
BS EN/IEC 60332-3-24



Temperature Limits
Fixed: -40°C to +70°C

Core Colours

[PAS5308 pair identification colour chart](#)

Standards

- PAS5308 / BS5308
- BS EN/IEC 60332-1-2
- BS EN/IEC 60228
- BS EN/IEC 60332-3-24

Construction

- **Conductor:** Under 1mm² Class 5 flexible copper conductor
1mm² & above Class 2 stranded copper conductor
- **Insulation:** Polyvinyl Chloride (PVC) Laid up to form pairs
- **Screen:** Aluminium/mylar foil tape individually screened pairs complete with 0.5mm drain wire
- **Overall Tape Screen:** Aluminium/Polyester Tape (AL/PET) with 0.5mm drain wire
- **Outer Sheath:** Polyvinyl Chloride (PVC)
- **Sheath Colour:** Blue or Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

PAS5308 Part2,Type1 Instrumentation Cable, Individually Screened - 0.5mm² to 1.5mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Pairs	Stranding(mm)	Outside Diameter(mm)	Weight(Kg/Km)	Brass A2 Gland
7312B	0.5	2	16/0.20	11	161	20S
7313B	0.5	5	16/0.20	14.2	253	25
7314B	0.5	10	16/0.20	20.1	408	32
7315B	0.5	20	16/0.20	26.3	753	40
7316BU	0.5	30	16/0.20	31.3	1153	40
7316BK	0.5	30	3016/0.20	31.3	1153	40
7317B	0.5	50	16/0.20	40.7	1190	50
7349B	0.75	2	24/0.20	11.8	184	20
7350B	0.75	5	24/0.20	15.3	299	25
7351B	0.75	10	24/0.20	21.7	489	32
7352B	0.75	20	24/0.20	28.8	920	40
7353B	0.75	30	24/0.20	34.5	1445	50S
7354B	0.75	50	24/0.20	44	2460	63S
7385B	1.5	2	7/0.53	13.7	242	242
7386B	1.5	5	7/0.53	17.8	408	408
7387B	1.5	10	7/0.53	25.5	714	714
7388B	1.5	20	7/0.53	33.4	1400	1400

PART 2 PAIR COLOURS

PAIR	A	B
1	White	Blue
2	White	Orange
3	White	Green
4	White	Brown
5	White	Grey
6	Red	Blue
7	Red	Orange
8	Red	Green
9	Red	Brown
10	Red	Grey
11	Black	Blue
12	Black	Orange
13	Black	Green
14	Black	Brown
15	Black	Grey
16	Yellow	Blue
17	Yellow	Orange
18	Yellow	Green
19	Yellow	Brown
20	Yellow	Grey
21	White/Blue	Blue
22	White/Blue	Orange
23	White/Blue	Green
24	White/Blue	Brown
25	White/Blue	Grey

PAIR	A	B
26	Red/Blue	Blue
27	Red/Blue	Orange
28	Red/Blue	Green
29	Red/Blue	Brown
30	Red/Blue	Grey
31	Blue/Black	Blue
32	Blue/Black	Orange
33	Blue/Black	Green
34	Blue/Black	Brown
35	Blue/Black	Grey
36	Yellow/Blue	Blue
37	Yellow/Blue	Orange
38	Yellow/Blue	Green
39	Yellow/Blue	Brown
40	Yellow/Blue	Grey
41	White / Orange	Blue
42	White / Orange	Orange
43	White / Orange	Green
44	White / Orange	Brown
45	White / Orange	Grey
46	Orange/Red	Blue
47	Orange/Red	Orange
48	Orange/Red	Green
49	Orange/Red	Brown
50	Orange/Red	Grey

For individual screened pairs, identification will be White/Blue numbered pairs.

Two pair collectively screened cables are in quad formation colour coded in rotation, Black, Blue, Green, Brown

Single triple will be Blue, White, Orange.

PART 2 ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA (MM ²)	MUTUAL CAPACITANCE pF/m		MINIMUM INSULATION RESISTANCE AT 20°C	MAXIMUM L/R RATIO
	Between Pairs or Adjacent Cores	Between any Core and Screen	mohms/km	μH/ohms
0.5	250	450	>25	25
0.75	250	450	>25	25
1	250	450	>25	25
1.5	250	450	>25	40

PART 2 CONDUCTOR RESISTANCE

NOMINAL CROSS SECTIONAL AREA (MM ²)	CONDUCTOR CLASS	MAXIMUM RESISTANCE CONDUCTOR AT 20 ⁰ C Ω/Km
0.5	5	39
0.75	5	26
1	1	18.1
1.5	2	12.1

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.