


## Silicon Flexible Cable VDE 0250 PT816 - 0.75mm - 2.5mm



The silicone flexible cable is mainly used in food processing plants and food processing related machinery. It can also be used in robotic applications where a higher temperature rating is required.

### Key Features



#### Installation Guidelines

Should not be installed at temperatures below 0°C or above +60°C



#### Voltage Rating

300/500 Volts



#### Minimum Bending Radius

As Per Manufacturers Datasheet



#### Temperature Limits

Temperature Range: -60°C to +180°C

### Construction

- **Conductor:** Flexible Tinned Annealed Copper Conductors
- **Insulation:** Silicone
- **Sheath:** Silicone

### Standards

- VDE 0250 PT816

### Core Colours

2 core -	Brown	Blue					
3 core -	Brown	Black	Grey				
4 core -	Brown	Black	Grey	Blue			
5 core -	Brown	Black	Grey	Green	Yellow		
6 core and above -	Black	cores with	White	numbers plus	Green	Yellow	

## Silicon Flexible Cable VDE 0250 PT816 - 0.75mm - 2.5mm - Dimensions

Reference	Conductor Size (mm <sup>2</sup> )	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Gland Size
BIHF2X1	0.75	2	32/0.20	6.7	59.9	20/16
BIHF2X/75	0.75	2	24/0.20	6.5	53.4	20/16
BIHF3X/75	0.75	3	24/0.20	6.9	63.7	20/16
BIHF4X/75	0.75	4	24/0.20	7.9	83.6	20/16
BIHF3X1	1	3	32/0.20	7.5	78.3	20/16
BIHF4X1	1	4	32/0.20	8.1	94.6	20S
BIHF2X1/5	1.5	2	30/0.25	7.6	82	20/16
BIHF3X1/5	1.5	3	30/0.25	8	98	20/16
BIHF4X1/5	1.5	4	30/0.25	8.8	122	20S
BIHF5X1/5	1.5	5	30/0.25	9.6	148	20S
BIHF2X2/5	2.5	2	50/0.25	8.9	135	20S
BIHF3X2/5	2.5	3	50/0.25	9.1	152	20S
BIHF4X2/5	2.5	4	50/0.25	10.1	188	20S

Multi core non-armoured 90 °C and 180°C thermosetting insulated flexible cables with sheath Reproduced from BS7671:2018 Wiring Regulations

TABLE 4F2B

VOLTAGE DROP (per ampere per metre):

Conductor operating temperature: 90 °C

Conductor cross-sectional area (mm <sup>2</sup> )	Two-core cable or 2 x Single core cables DC (mV/Nm)	2 core cable, single-phase AC (mV/Nm)			1 x 3 core, 4 core or 5 core cable, three-phase AC (mV/Nm)			2 single-core cables, touching Single-phase AC* (mV/Nm)		
4	13.20	13.20			11.10			-		
6	8.50	8.50			7.40			-		
10	5.10	5.10			4.40			-		
16	3.20	3.20			2.70			-		
		r	x	z	r	x	z	r	x	z
25	2.03	2.03	0.175	2.04	1.73	0.150	1.73	-	-	-
35	1.420	-	-	-	1.22	0.150	1.23	1.44	0.21	1.46
50	1.000	-	-	-	0.91	0.145	0.93	1.00	0.21	1.02
70	0.710	-	-	-	0.62	0.140	0.64	0.71	0.20	0.73
95	0.540	-	-	-	0.47	0.135	0.49	0.54	0.195	0.57
120	0.420	-	-	-	0.37	0.135	0.39	0.42	0.190	0.46
150	0.340	-	-	-	0.29	0.130	0.32	0.34	0.190	0.39
185	0.270	-	-	-	0.24	0.130	0.27	0.27	0.190	0.33
240	0.210	-	-	-	0.188	0.130	0.23	0.210	0.185	0.28
300	0.167	-	-	-	0.147	0.125	0.195	0.173	0.180	0.25
400	0.127	-	-	-	-	-	-	0.132	0.175	0.22
500	0.100	-	-	-	-	-	-	0.107	0.170	0.20
630	0.074	-	-	-	-	-	-	0.085	0.170	0.190

NOTES:

<sup>1</sup> The voltage drop figures given above are based on a conductor operating temperature of 90 °C and are therefore not accurate when the operating temperature is in excess of 90 °C. In the case of the 180 °C cables with a conductor temperature of 150 °C the above resistive values should be increased by a factor of 1.2.

<sup>2</sup> \*A larger voltage drop will result if the cables are spaced.

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

For more information contact: 01642 241 133

