


SY Control Flex - Temporary Power Leads



Description

Pre-cut & bespoke PVC SY Control cable with a large range of connectors. Flexible, with a high resistance to mechanical stress. For the events/generator industries & film/theatre applications. Available in both single and 3 phase 230V-415V. 3 and 5 core from 2.5mm up to 50mm and single core from 50mm up to 240mm. Cut in standard lengths of 5, 10, 15, 20 and 25 metres or bespoke to customers individual requirements. We can also produce as lug to lug or powerlock to lug.

Key Features

Core Colours

2 core



3 core



4 core



5 core



Standards

Construction

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance



SY Control Flex - Temporary Power Leads - Dimensions

Reference
Test1

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.